C class Product Information

GHC631WH

MODEL		GHC631WH
Energy efficiency classes of domestic range hoods (A-G)		
Annual Energy Consumption - AEC hood (kWh/a)	С	
	51,3	
Fluid Dynamic Efficiency classes for domestic range hoods (A-G)	E	
Lighting Efficiency classes (A-G)	D	
The Grease Filtering Efficiency classes (A-G)	E	
 Sound power level L WA - (dB)	65	
Time increase factor - f	1,7	
Fluid Dynamic Efficiency - FDE hood	8,5	
Energy Efficiency Index - EEI hood	84,9	
Measured air flow rate at best efficiency point - Q BEP (m 3 /h)	138,2	
Measured air pressure at best efficiency point P BEP (Pa)	173,4	
Measured electric power input at best efficiency point - W BEP (W)	78	
Nominal power of the lighting system - W L (W)	4	
Average illumination of the lighting system on the cooking surface - E middle (lux)		
Lighting Efficiency LE hood - (lux/Watt)		
Gerase Filtering Efficiency GFE hood - (%)	78	
Minimum airflow (Q min)	m³/h	
Maximum air flow - Q max (m 3 /h)	230m ³ /h	
Airflow -boost (Q boost)	-	
Minimum sound power level LWA - (dB)	45dB	
Maximum sound power level L WA - (dB)	65dB	
Sound power level-boost L WA - (dB)	-	
Measured power consumption off mode P o (W)	0	
Measured power consumption in standby mode - P s (W)	0	

Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014 "