C class Product Information GHC931WH

| MODEL | GHC931WH |
|---|--|
| | |
| Energy efficiency classes of domestic range hoods (A-G) | С |
| Annual Energy Consumption - AEC hood (kWh/a) | 50,7 |
| Fluid Dynamic Efficiency classes for domestic range hoods (A-G) | E |
| Lighting Efficiency classes (A-G) | D |
| The Grease Filtering Efficiency classes (A-G) | E |
| Sound power level L WA - (dB) | 65 |
| Time increase factor - f | 1,7 |
| Fluid Dynamic Efficiency - FDE hood | 8,8 |
| Energy Efficiency Index - EEI hood | 84,6 |
| Measured air flow rate at best efficiency point - Q BEP (m 3 /h) | 139,2 |
| Measured air pressure at best efficiency point P BEP (Pa) | 175,4 |
| Measured electric power input at best efficiency point - W BEP (W) | 78 |
| Nominal power of the lighting system - W L (W) | 4 |
| Average illumination of the lighting system on the cooking surface - E middle (lux) |) |
| Lighting Efficiency LE hood - (lux/Watt) | |
| Gerase Filtering Efficiency GFE hood - (%) | 78 |
| Minimum airflow (Q min) | m³/h |
| Maximum air flow - Q max (m 3 /h) | 233m³/h |
| Airflow -boost (Q boost) | <u> - </u> |
| Minimum sound power level L WA - (dB) | 45dB |
| Maximum sound power level L WA - (dB) | 65dB |
| Sound power level-boost L WA - (dB) | - |
| Measured power consumption off mode P o (W) | 0 |
| Measured power consumption in standby mode - P s (W) | 0 |