

C class

Product Information
GHP645IX

MODEL

GHP645IX

Energy efficiency classes of domestic range hoods (A-G)	C
Annual Energy Consumption - AEC hood (kWh/a)	62,6
Fluid Dynamic Efficiency classes for domestic range hoods (A-G)	C
Lighting Efficiency classes (A-G)	A
The Grease Filtering Efficiency classes (A-G)	C
Sound power level L WA - (dB)	67
Time increase factor - f	1,3
Fluid Dynamic Efficiency - FDE hood	18,1
Energy Efficiency Index - EEI hood	73,2
Measured air flow rate at best efficiency point - Q BEP (m ³ /h)	300,7
Measured air pressure at best efficiency point P BEP (Pa)	259,7
Measured electric power input at best efficiency point - W BEP (W)	119,6
Nominal power of the lighting system - W L (W)	8
Average illumination of the lighting system on the cooking surface - E middle (lux)	
Lighting Efficiency LE hood - (lux/Watt)	
Grease Filtering Efficiency GFE hood - (%)	82,8
Minimum airflow (Q min)	m ³ /h
Maximum air flow - Q max (m ³ /h)	498.3m ³ /h
Airflow -boost (Q boost)	-
Minimum sound power level L WA - (dB)	62dB
Maximum sound power level L WA - (dB)	67dB
Sound power level-boost L WA - (dB)	-
Measured power consumption off mode P o (W)	0
Measured power consumption in standby mode - P s (W)	0

Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014 "