

| Category   | Art. 12.5 reference | Identifier Key Field Name                   | Description   | Enter here value of the measured parameter, result of calculation or text   | Unit             | Data Type*            | Product Specific Legal Reference                          | Comments for suppliers and market surveillance   |
|--|---------------------|---|---|---|------------------|-----------------------|---|--|
| Generic data   | 5a                  | MODEL_IDENTIFIER                            | General description of the model, for unequivocal identification  | GHBS97IX  | model identifier | STRING/256            | n/a   |  |
|  | 5b                  | COMP_STDREFERENCE                           | Reference to the harmonised or other standards applied  | EN 61591:1997 /A1:2006 /A2:2011 /A11:2014/A12:2015; EN 60704-1: 2010 / A11: 2012; EN 60704-2-13: 2017; EN 50564: 2011 | Text             | STRING/4000           | n/a   |  |
|  | 5c                  | COMP_SPECIF_PRECAUTIONS                     | Specific precautions   optional can be empty  | -   | Text             | STRING/4000           | n/a   |  |
|  | 5f                  | COMP_TEST_COND                              | Testing conditions, other than in above mentioned standard   optional can be empty                                  | -   | Text             | STRING/4000           | n/a   |  |
|  | 5e**                | COMP_EEhood                                 | the Energy Efficiency Index (EEIhood)   | 52.2  | -                | NUM/1                 | 65/2014, Annex V B.1 (c) (1)                              | for calculation details/formula see reference in column H  |
|  | 5e**                | COMP_AEChood                                | the Annual Energy Consumption (AEChood)   | 45.3  | kWh/annum        | NUM/1                 | 65/2014, Annex V B.1 (c) (3)                              | for calculation details/formula see reference in column H  |
| Measured, declared and calculated technical parameters | 5e**                | COMP_f                                      | the time increase factor (f)  | 0.9   | unitless         | NUM/1                 | 65/2014, Annex V B.1 (c) (4)                              | for calculation details/formula see reference in column H  |
|  | 5e**                | COMP_FDEhood                                | the Fluid Dynamic Efficiency (FDEhood)  | 29.5  | %                | NUM/1                 | 65/2014, Annex V B.1 (c) (5)                              | for calculation details/formula see reference in column H  |
|  | 5d                  | COMP_QBEP                                   | the measured flow rate of the domestic range hood at the best efficiency point (QBEP)                               | 364.4   | m³/h             | NUM/1                 | 65/2014, Annex V B.1 (c) (7)                              |  |
|  | 5d                  | COMP_PBEP                                   | the measured value of the static pressure difference of the domestic range hood at the best efficiency point (PBEP) | 373   | Pa               | INTEGER               | 65/2014, Annex V B.1 (c) (8)                              |  |
|  | 5d                  | COMP_WBEP                                   | the measured value of the electric power input of the domestic range hood at the best efficiency point (WBEP)       | 128.1   | Watt             | NUM/1                 | 65/2014, Annex V B.1 (c) (9)                              |  |
|  | 5d                  | COMP_Emiddle                                | the average illumination of the lighting system on the cooking surface (Emiddle)                                    | 80  | lux              | INTEGER               | 65/2014, Annex V B.1 (c) (10)                             |  |
|  | n/a                 | COMP_WL                                     | the nominal power consumption of the lighting system on the cooking surface (WL)                                    | 2.0   | Watt             | NUM/1                 | 65/2014, Annex V B.1 (c) (11)                             | this value is not measured but it is the nominal one.  |
|  | 5e**                | COMP_LEhood                                 | the measured value of the Lighting Efficiency (LEhood)  | 40  | Lux/Watt         | INTEGER               | 65/2014, Annex V B.1 (c) (12)                             | calculated according to point 2 of Annex II, in lux/Watt and rounded to the nearest integer        |
|  | 5d                  | COMP_GFEhood                                | the measured value of the Grease Filtering Efficiency (GFE hood)  | 74.0  | %                | NUM/1                 | 65/2014, Annex V B.1 (c) (14)                             |  |
|  | 5d                  | COMP_Po                                     | if applicable the power consumption in off mode (Po)  | 0.00  | Watt             | NUM/2                 | 65/2014, Annex V B.1 (c) (16)                             |  |
|  | 5d                  | COMP_Ps                                     | if applicable the power consumption in standby mode (Ps)  | 0.49  | Watt             | NUM/2                 | 65/2014, Annex V B.1 (c) (17)                             |  |
|  | 5d                  | COMP_dBmin                                  | the airborne acoustical A-weighted sound power emissions at minimum speed   | 48  | dBa              | INTEGER               | 65/2014, Annex V B.1 (c) (18)                             | Noise measurements and declarations are complex. Please refer to details in the relevant standard. |
|  | 5d                  | COMP_dBmax                                  | the airborne acoustical A-weighted sound power emissions at maximum speed   | 63  | dBa              | INTEGER               | 65/2014, Annex V B.1 (c) (18)                             | Noise measurements and declarations are complex. Please refer to details in the relevant standard. |
|  | 5d                  | COMP_dBboost                                | if present, the airborne acoustical A-weighted sound power emissions at intensive or boost setting                  | 68  | dBa              | INTEGER               | 65/2014, Annex V B.1 (c) (19)                             |  |
|  | 5d                  | COMP_Qmin                                   | the air flow values of the domestic range hood at minimum speed   | 286.0   | m³/h             | NUM/1                 | 65/2014, Annex V B.1 (c) (20)                             |  |
|  | 5d                  | COMP_Qmax                                   | the air flow values of the domestic range hood at maximum speed   | 564.0   | m³/h             | NUM/1                 | 65/2014, Annex V B.1 (c) (20)                             |  |
|  | 5d                  | COMP_Qboost                                 | if present, the air flow value of the domestic range hood at intensive or boost setting                             | 679.0   | m³/h             | NUM/1                 | 65/2014, Annex V B.1 (c) (21)                             |  |
| 5e**   | COMP_SAEChood       | Standard Annual Energy Consumption SAEChood | 86.9  | kWh/a   | NUM/1            | 65/2014, Annex II 2.1 | for calculation details/formula see reference in column H |  |

\*\*\*) Calculations are performed in accordance with the specifications/requirements of the respective parts in the Annexes of the corresponding Delegated Acts and/or with the applicable standards.

\*) Explanation for the data-type column

There are several notations for how to distinguish between data types, none of them universal. For these templates we use the following notations

Numeric

INTEGER --> non-fractional (natural) number, here only positive, eg 3, 190, 0, 55...

NUM/x, where 'x' is an integer --> a floating point decimal number, where x is the number of fixed digits, eg NUM/2 could be 2.32 or 0.10 or 3.00, the value must have the expected numbers of digits

NB: actually NUM/0 equals integer, however, for clarity we use INTEGER for NUM/0.

FLOAT --> any a floating point decimal number, with no predefined number of fixed digits

Alphanumeric

STRING/x, where 'x' is an integer --> a sequence of x alphanumeric characters. The alphanumeric character could be any of the alphabet or any special character, except (to be future proof the following reserved XML characters < & (possibly also > ' " and should also be avoided, but that will depend on the EPREL XML parser.

Other data types

BOOLEAN --> logical value, can be either TRUE or FALSE

ENUM --> is a list of fixed and defined values, values are usually strings or characters (notation also used in EPREL documentation), eg ENUM --> 'A+++', 'A++', 'A+', 'A', 'B', 'C', 'D', in this template the list is given as comment 1.